

METAL SOUND PROJECTORS



➤ **CELL 10/T**

➤ **CELL 10/TC**

TECHNICAL SPECIFICATIONS


Rated power, Watts	10
Tappings 100 volt line, Watts	10/5/2.5/1.25
Transformer Impedance, Ohms, 100V	1k/2k/4k/8k
Tappings 70.7 volt line, Watts	5/2.5/1.25/0.375
Driver impedance, Ohms	8
Effective frequency range, Hz (BSEN60268-5)	120 – 18,000
S.P.L. @ 1m, 1 watt, dB, Test Signal Bandwidth 100Hz-10 kHz	91
S.P.L. @ Full power Octave Bandwidth, dB	101
Acoustic Power (dB-PWL@1 Watt) 1k/2k Hz, dB	87/90
Dispersion at 1k/2k Hz, Degrees	180/120
Directivity Axial Q factor, 1k/2kHz	2.8/5.9
Dimensions, front & depth, mm	Ø140 x 191
Net weight, Kgs	1.9
Colour/Finish	White RAL9016
Material	Aluminium with Stainless steel hardware
Mounting	Aluminium U bracket

➤ CELL10/TC is BS5839 Part 8 voice alarm compliant


EASE, CATT, ULYSSES and Architectural specifications are supplied on the disc inserted at the back of this folder
 Manufacturer reserves the right to alter specifications without notice – March 2007

> **CELL10/T** > **CELL10/TC** METAL SOUND PROJECTORS


side view
unit: **mm**




front view
unit: **mm**



circuit diagram
CELL10/T



speech octave band sensitivity



Effective Frequency Range **CELL10/T CELL10/TC** 120Hz - 18,000Hz



Penton UK Ltd

Unit 2 Teville Industrials | Dominion Way | Worthing | West Sussex | BN14 8NW

T: +44 (0)1903 215315 | F: +44(0)1903 215415 | E: SALES@PENTONUK.CO.UK

www.penton.org